
























Options

Surface Mount and Wraparound

| Item | Catalog No. | Description | For Use With |
|---|-------------|---|---|
|  | ITB4 | Hanger for mounting close to ceiling on T-bar grid system. | All surface mounted fixtures. |
|  | CS4 | All purpose spacer (1 1/2" x 2 1/4" x 4"). | Maintains 1 1/2" space between fixture and ceiling on any type installation. |
|  | CS5 | All purpose spacer with special T-Bar clip and stud for mounting to inverted T-Bar ceiling. | Maintains 1 1/2" between fixture and T-Bar ceiling. |
|  | CS2 | Ceiling spacer for mounting directly to outlet box. Used for mounting fixtures below combustible low density cellulose fiberboard ceilings. | Maintains 1 1/2" between top of fixture channel and the ceiling surface to be used when mounted directly to outlet box. |
|  | S18 | Swivel canopy, 1-18" stem - All white finish, 8° swivel. | Individual or continuous row mounting of all commercial fixtures, using knockouts near end of fixtures. |
| | C18 | Swivel canopy only - All white finish, 8° swivel. | |
| | S018 | 1-18" stem only - All white finish. | |
|  | AWC5 | 5" diameter 3/8" deep canopy for use when mounting AW under an outlet box. | AWN Series |
|  | NL | Medium base lampholder for 15, 20, 40 or 60 watt T10 lamp. Lamp not included. 120V only. | WP, WC, AWN, SM and WAL Series. |
|  | PL7 | Fluorescent night light for 7W T-4 G23 lamp. Lamp not included. PL ballast will default to fixture voltage unless specified. | J, SG, F, SM and WAL series. |
| | PL9 | Fluorescent night light for 9W T-4 G23 lamp. Lamp not included. PL ballast will default to fixture voltage unless specified. | J, SG, F, SM and WAL series. |
| | PL13 | Fluorescent night light for 13W T-4 G23 lamp. Lamp not included. PL ballast will default to fixture voltage unless specified. | J, SG, F, SM and WAL series. |
|  | WSC | Wrap safety chains for securing plastic diffuser to fixture housing. (2 chains and clips). | All RO and AW series. |
|  | S18D | Double canopy (2) 18" stems. | All 4' units in RO and PT series. |

Options

Industrial Accessories

| Item | Catalog No. | Description | For Use With |
|---|--------------------------|--|---|
|  | CSRAC KLVRAC KLRAC | Full range aligners (set of 2) for aligning reflector flanges and closing gap between two reflectors. Indicate row arrangement when ordering | CSR KPV-KPL KP-KL |
|  | KLWG4 CSRWG4 | Welded wire lamp guard - 4 ft. Two required for 8' units. Welded wire lamp guard - 4 ft. Two required for 8' units. | Titan, Titan-V, and Dynamo Industrial series. CSR series. |
|  | KLEGG | Metal egg crate louver. Two required for 8' units. | Titan and Dynamo Industrial series. |
|  | KLK | Gym kit bracket, bag of 4. | L-2 louver when used in gyms with Titan and Dynamo. |
|  | KLFS12 | Framed Dyma-Lens acrylic shielding. Two required for 8' units. Note: cannot be combined with the KLWG4 | Titan and Dynamo Industrial series. |
|  | KLEC | Reflector end enclosure (per end). Baked white enamel. | Titan, Titan-V, and Dynamo Industrial series. |
|  | C&P | 6 ft. 3 conductor cord & plug set (120V or 277V) installed. | All industrial fixtures. Cord and plug installed in end plate unless otherwise specified. (Based on #18SJT cord). |
|  | PSW | Economy pull switch. Wired but not installed. 120V only. | Strip lites and Industrials. Contact factory for application. |
|  | RIF | Radio Interference Filter — 120/277 Volt. | All fixtures. |
|  | GLR | Fast Blow fuse and holder for 120V or 277V. | All fixtures. |
|  | GMF | Slow Blow fuse and holder for 120V or 277V. | All fixtures. |
|  | SSHK | Stainless steel hanging kit (Chain not included.) | LU, LUN series. WL or DMR |
|  | HUBK | Stem Hanging Kit consists of 2 die cast hubs, 2 "O" rings & locknuts. Hubs are threaded for 1/2" pipe. Housings must be drilled to install hubs. | LU, LUN, DMR. (Without hub on end). |

Notes: 1. Cord sets consist of No. 18/3 SJT cord with an integral molded straight blade cap for 120V and a metal straight end blade cap for 277V. All with grounding blade. The above are not compatible with 47 Series, consult your Columbia representative for available options on the 47 Series.